

2015 FORD FUSION TECHNICAL SPECIFICATIONS

BODY		Four-door sedan			
Construction	Unitized steel body				
Final assembly location	Hermosillo, Mexico; Flat Rock, Michigan				
POWERTRAIN AND CHASSIS					
GASOLINE ENGINES					
Type	2.5-liter inline four-cylinder	1.5-liter EcoBoost® inline four-cylinder	2.0-liter EcoBoost inline four-cylinder		
Manufacturing location	Chihuahua, Mexico	Craiova, Romania	Valencia, Spain		
Configuration	Aluminum block and head	Aluminum block and head	Aluminum block and head		
Valvetrain	DOHC, four valves per cylinder, intake variable camshaft timing	DOHC, four valves per cylinder, twin independent variable camshaft timing	DOHC, four valves per cylinder, twin independent variable camshaft timing		
Bore x stroke	3.50 x 3.94 in.	3.11 x 3.00 in.	3.44 x 3.27 in.		
Displacement	152 cu. in./2,488 cc	91.5 cu. in./1,499 cc	122 cu. in./1,999 cc		
Compression ratio	9.7:1	10.0:1	9.3:1		
Horsepower	175 @ 6,000 rpm	181 @ 6,000 rpm	240 @ 5,500 rpm		
Torque	170 lb.-ft. @ 4,500 rpm	185 lb.-ft. @ 2,700 rpm	270 lb.-ft. @ 3,000 rpm		
Fuel	87 octane	87 octane	87 octane (minimum) 91+ recommended		
Fuel capacity	16.5 gallons	16.5 gallons	16.5 gallons FWD, 17.5 gallons AWD		
Fuel injection	Sequential multiport electronic	Turbocharged direct gasoline injection	Turbocharged direct gasoline injection		
Oil capacity	5.7 quarts with filter	4.0 quarts with filter	5.7 quarts with filter		
DRIVETRAIN					
Layout	Front-wheel drive, transverse	Front-wheel drive, transverse	Front-wheel drive/all-wheel drive, transverse		
TRANSMISSION					
Type	6F35 six-speed SelectShift Automatic	6F35 six-speed SelectShift Automatic	6F35 6-speed SelectShift Automatic		
GEAR RATIOS					
1st	4.58	4.58	4.58		
2nd	2.96	2.96	2.96		
3rd	1.91	1.91	1.91		
4th	1.45	1.45	1.45		
5th	1.00	1.00	1.00		
6th	0.75	0.75	0.75		
Final drive	3.07:1	3.07:1	3.21:1 FWD	3.36:1 AWD	
SUSPENSION					
Front	Independent MacPherson strut with stabilizer bar				
Rear	Independent integral link with stabilizer bar				
STEERING					
Type	Rack-and-pinion with electric power-assisted steering				
Ratio	14.8 to 1				

2015 FORD FUSION TECHNICAL SPECIFICATIONS

Turns, lock-to-lock	2.7
BRAKES	
Type	Power-assisted, four-channel, four-wheel disc with ABS and AdvanceTrac® electronic stability control
Front	11.8 x 1.10-in. vented disc
Rear	11.8 x .43-in. solid disc
WHEELS AND TIRES	
S	16-in. sparkle silver aluminum, 215/60HR16 BSW
SE	17-in. sparkle silver painted aluminum, 235/50R17 BSW
	Optional 18-in. premium painted aluminum, 235/45R18 BSW Optional 18-in. premium Luster Nickel painted aluminum Optional 18-in. black gloss aluminum Optional 18-in. five-spoke machined face painted aluminum
Titanium	18-in. polished-face premium painted aluminum, 235/45VR18 BSW
	Optional 18-in. five-spoke machined face painted aluminum Optional 19-in. H-spoke painted aluminum, 235/40R19
DIMENSIONS (inches unless otherwise noted)	
EXTERIOR	
Wheelbase	112.2
Length	191.7
Width	75.2 folded mirrors/83.5 including mirrors
Height	58.0
Track, front/rear	62.3/62.0
INTERIOR	
Seating capacity	Five
First row headroom	39.2
First row legroom, maximum	44.3
First row shoulder room	57.8
First row hip room	55.0
Second row headroom	37.8
Second row legroom	38.3
Second row shoulder room	56.9
Second row hip room	54.4
WEIGHTS AND CAPACITIES (POUNDS)	
Base curb weight, 2.5-liter	3,461
Base curb weight, 1.5-liter	3,438
Base curb weight, 2.0-liter	3,322 FWD, 3,821 AWD
Total EPA volume	118.8 cu. ft.
Cargo space	16.0 cu. ft.
FUEL EFFICIENCY (MPG)¹	
2.5-liter I-4, six-speed automatic	22 mpg city/34 highway mpg/26 mpg combined
1.5-liter EcoBoost, six-speed automatic	24 mpg city/36 highway mpg/28 mpg combined
1.5-liter EcoBoost, six-speed automatic, auto start-stop	25 mpg city/37 highway mpg/29 mpg combined
2.0-liter EcoBoost, six-speed automatic	22 mpg city/33 highway mpg/26 mpg combined
2.0-liter EcoBoost,	22 mpg city/31 highway mpg/25 mpg combined

¹ 2015 model year EPA-estimated fuel economy ratings, actual mileage will vary

**2015 FORD FUSION
TECHNICAL SPECIFICATIONS**

all-wheel-drive, six-speed automatic	
---	--

Specifications subject to change