

2015 KIA SEDONA SPECIFICATIONS

	L	LX	EX	SX	SX Limited
ENGINE					
TYPE	3.3-liter V6 GDI, aluminum heads and aluminum block	3.3-liter V6 GDI, aluminum heads and aluminum block	3.3-liter V6 GDI, aluminum heads and aluminum block	3.3-liter V6 GDI, aluminum heads and aluminum block	3.3-liter V6 GDI, aluminum heads and aluminum block
VALVE SYSTEM	DOHC, 4 valves/cylinder	DOHC, 4 valves/cylinder	DOHC, 4 valves/cylinder	DOHC, 4 valves/cylinder	DOHC, 4 valves/cylinder
BORE X STROKE	92mm x 83.8 mm	92mm x 83.8 mm	92mm x 83.8 mm	92mm x 83.8 mm	92mm x 83.8 mm
DISPLACEMENT	3,342 cc	3,342 cc	3,342 cc	3,342 cc	3,342 cc
COMPRESSION RATIO	11.5:1	11.5:1	11.5:1	11.5:1	11.5:1
HORSEPOWER (SAE NET)	276 hp @ 6,000 rpm	276 hp @ 6,000 rpm	276 hp @ 6,000 rpm	276 hp @ 6,000 rpm	276 hp @ 6,000 rpm
TORQUE (SAE NET)	248 lb.-ft @ 5,200 rpm	248 lb.-ft @ 5,200 rpm	248 lb.-ft @ 5,200 rpm	248 lb.-ft @ 5,200 rpm	248 lb.-ft @ 5,200 rpm
EMISSION CONTROL SYSTEM	WCC + UCC	WCC + UCC	WCC + UCC	WCC + UCC	WCC + UCC
IGNITION	Electronic Positive Ignition	Electronic Positive Ignition	Electronic Positive Ignition	Electronic Positive Ignition	Electronic Positive Ignition
FUEL SYSTEM	High pressure direct fuel injection	High pressure direct fuel injection	High pressure direct fuel injection	High pressure direct fuel injection	High pressure direct fuel injection
FUEL PUMP	Electromagnetic, high pressure mechanical	Electromagnetic, high pressure mechanical	Electromagnetic, high pressure mechanical	Electromagnetic, high pressure mechanical	Electromagnetic, high pressure mechanical
FUEL REQUIREMENT	Regular unleaded	Regular unleaded	Regular unleaded	Regular unleaded	Regular unleaded
FUEL TANK CAPACITY	21.1 gal./ 80 liters	21.1 gal./ 80 liters	21.1 gal./ 80 liters	21.1 gal./ 80 liters	21.1 gal./ 80 liters
COOLING SYSTEM	Liquid cooled	Liquid cooled	Liquid cooled	Liquid cooled	Liquid cooled
COOLANT CAPACITY	4.4 liters	4.4 liters	4.4 liters	4.4 liters	4.4 liters

ENGINE OIL CAPACITY	5.2 liters	5.2 liters	5.2 liters	5.2 liters	5.2 liters
----------------------------	------------	------------	------------	------------	------------

DRIVETRAIN

TRANSMISSION	Electronically controlled 6-speed automatic, overdrive	Electronically controlled 6-speed automatic, overdrive	Electronically controlled 6-speed automatic, overdrive	Electronically controlled 6-speed automatic, overdrive	Electronically controlled 6-speed automatic, overdrive
GEAR RATIOS	A/T	A/T	A/T	A/T	A/T
FIRST	4.252:1	4.252:1	4.252:1	4.252:1	4.252:1
SECOND	2.654:1	2.654:1	2.654:1	2.654:1	2.654:1
THIRD	1.804:1	1.804:1	1.804:1	1.804:1	1.804:1
FOURTH	1.386:1	1.386:1	1.386:1	1.386:1	1.386:1
FIFTH	1.000:1	1.000:1	1.000:1	1.000:1	1.000:1
SIXTH	0.772:1	0.772:1	0.772:1	0.772:1	0.772:1
REVERSE	3.393:1	3.393:1	3.393:1	3.393:1	3.393:1
FINAL DRIVE RATIO	3.041:1	3.041:1	3.041:1	3.041:1	3.041:1

ELECTRICAL

BATTERY	12V, 80AH, 660CCA	12V, 80AH, 660CCA	12V, 80AH, 660CCA	12V, 80AH, 660CCA	12V, 80AH, 660CCA
ALTERNATOR	13.5V, 150 amp	13.5V, 150 amp	13.5V, 150 amp	13.5V, 150 amp	13.5V, 150 amp
STARTER	12V, 1.7 kW	12V, 1.7 kW	12V, 1.7 kW	12V, 1.7 kW	12V, 1.7 kW

EXTERIOR DIMENSIONS

WHEELBASE	120.5 in.	120.5 in.	120.5 in.	120.5 in.	120.5 in.
OVERALL LENGTH	201.4 in.	201.4 in.	201.4 in.	201.4 in.	201.4 in.

OVERALL WIDTH (WITH SIDE MIRRORS)	89.3 in.	89.3 in.	89.3 in.	89.3 in.	89.3 in.
OVERALL WIDTH (WITHOUT SIDE MIRRORS)	78.1 in.	78.1 in.	78.1 in.	78.1 in.	78.1 in.
OVERALL HEIGHT	68.5 in. (69.1 with Roof rack)	68.5 in. (69.1 with Roof rack)	68.5 in. (69.1 with Roof rack)	68.5 in. (69.1 with Roof rack)	68.5 in. (69.1 with Roof rack)
TRACK (FRONT/REAR)	68.5 in. / 68.8 in.	68.5 in. / 68.8 in.	68.5 in. / 68.8 in.	68.5 in. / 68.8 in.	68.5 in. / 68.8 in.
GROUND CLEARANCE (IN.)	6.7 in.	6.7 in.	6.7 in.	6.7 in.	6.7 in.

INTERIOR DIMENSIONS

SEATING CAPACITY	7	7 / 8 optional	8	8	7
HEAD ROOM (WITHOUT SUNROOF)	-	-	-	-	-
FRONT	39.8 in.	39.8 in.	39.8 in.	39.8 in.	-
2ND ROW	39.4 in.	39.4 in.	39.4 in.	39.4 in.	-
3RD ROW	38.9 in.	38.9 in.	38.9 in.	38.9 in.	-
HEAD ROOM (WITH SUNROOF)	-	-	-	-	-
FRONT	-	-	-	-	38.7 in.
2ND ROW	-	-	-	-	37.4 in.
3RD ROW	-	-	-	-	36.6 in.
SHOULDER ROOM	-	-	-	-	-
FRONT	63.9 in.	63.9 in.	63.9 in.	63.9 in.	63.9 in.

2ND ROW	63.1 in.	63.1 in.	63.1 in.	63.1 in.	63.1 in.
3RD ROW	59.4 in.	59.4 in.	59.4 in.	59.4 in.	59.4 in.
LEGROOM	-	-	-	-	-
FRONT	40.9 in.	40.9 in.	40.9 in.	40.9 in.	40.9 in.
2ND ROW	41.1 in.	41.1 in.	41.1 in.	41.1 in.	40.6 in.
3RD ROW	34.8 in.	34.8 in.	34.8 in.	34.8 in.	34.8 in.
HIP ROOM	-	-	-	-	-
FRONT	59.3 in.	59.3 in.	59.3 in.	59.3 in.	59.3 in.
2ND ROW	66.1 in.	66.1 in.	66.1 in.	66.1 in.	66.1 in.
3RD ROW	50.0 in.	50.0 in.	50.0 in.	50.0 in.	50.0 in.
INTERIOR VOLUME TOTAL (SAE)	-	-	-	-	-
CARGO (BEHIND 1ST ROW)	142.0 cu. ft.	142.0 cu. ft.	142.0 cu. ft.	142.0 cu. ft.	142.0 cu. ft.
CARGO (BEHIND 2ND ROW)	78.4 cu. ft.	78.4 cu. ft.	78.4 cu. ft.	78.4 cu. ft.	78.4 cu. ft.
CARGO (BEHIND 3RD ROW)	33.9 cu. ft.	33.9 cu. ft.	33.9 cu. ft.	33.9 cu. ft.	33.9 cu. ft.
LUGGAGE CARGO CAPACITY (CR)	62.1 cu. ft.	62.1 cu. ft.	62.1 cu. ft.	62.1 cu. ft.	-

BODY & CHASSIS

LAYOUT	Front engine, front-wheel drive	Front engine, front-wheel drive	Front engine, front-wheel drive	Front engine, front-wheel drive	Front engine, front-wheel drive
BODY TYPE	Steel unibody	Steel unibody	Steel unibody	Steel unibody	Steel unibody

FRONT SUSPENSION	MacPherson struts, coil springs, anti-roll bar	MacPherson struts, coil springs, anti-roll bar	MacPherson struts, coil springs, anti-roll bar	MacPherson struts, coil springs, anti-roll bar	MacPherson struts, coil springs, anti-roll bar
REAR SUSPENSION	Multi-link with struts, coil springs	Multi-link with struts, coil springs	Multi-link with struts, coil springs	Multi-link with struts, coil springs	Multi-link with struts, coil springs
STEERING TYPE	Rack-and-pinion, Hydraulic power-assisted	Rack-and-pinion, Hydraulic power-assisted	Rack-and-pinion, Hydraulic power-assisted	Rack mounted MDPS	Rack mounted MDPS
TURNS, LOCK-TO-LOCK	3.16	3.16	3.16	3.16	3.16
TURNING CIRCLE, CURB-TO-CURB	36.8 ft.	36.8 ft.	36.8 ft.	36.8 ft.	36.8 ft.

BRAKES

TYPE	Hydraulic, Power-assisted vacuum with Anti-Lock Brakes (ABS)	Hydraulic, Power-assisted vacuum with Anti-Lock Brakes (ABS)	Hydraulic, Power-assisted vacuum with Anti-Lock Brakes (ABS)	Hydraulic, Power-assisted vacuum with Anti-Lock Brakes (ABS)	Hydraulic, Power-assisted vacuum with Anti-Lock Brakes (ABS)
FRONT	12.6 in. vented discs brakes	12.6 in. vented discs brakes	12.6 in. vented discs brakes	12.6 in. vented discs brakes	12.6 in. vented discs brakes
REAR	11.9 in. solid disc brakes	11.9 in. solid disc brakes	11.9 in. solid disc brakes	11.9 in. solid disc brakes	11.9 in. solid disc brakes

TIRES & WHEELS

TIRES	235/65R17	235/65R17	235/60R18	235/60R18	235/55R19
WHEELS	6.5J x 17 alloy	6.5J x 17 alloy	6.5J x 18 alloy	6.5J x 18 machine alloy	6.5J x 19 chrome alloy

CURB WEIGHT

STANDARD - MINIMUM	4,414 lbs.	4,411 lbs.	4,539 lbs.	4,548 lbs.	4,656 lbs.
FULL OPTION - MAXIMUM	4,720 lbs.	4,720 lbs.	4,720 lbs.	4,720 lbs.	4,720 lbs.
WEIGHT DISTRIBUTION (FRONT / REAR)	57% / 43%	57% / 43%	57% / 43%	57% / 43%	57% / 43%

TOWING CAPACITY

TOWING CAPACITY	3500 lbs.	3500 lbs.	3500 lbs.	3500 lbs.	3500 lbs.
------------------------	-----------	-----------	-----------	-----------	-----------

ESTIMATED FUEL ECONOMY

CITY	18 mpg	18 mpg	18 mpg	18 mpg	17 mpg
HIGHWAY	24 mpg	24 mpg	24 mpg	25 mpg	22 mpg
COMBINED	20 mpg	20 mpg	20 mpg	21 mpg	19 mpg